Amendment to the Claims:

1. (Currently Amended) ~~Rotating~~ A rotating case [[(1)]] ~~requiring~~ comprising:

a base [[(2)]] mounted movably for axial rotation around a tubular body; [[(3)]] ~~to interior of which is movably mounted for~~

a slide [[(4)]] ~~destined~~ adapted to receive ~~the lip~~stick [[(100)]] movably mounted in an interior of the tubular body, the base [[(2)]] ~~requiring~~ including a means of guidance [[(20)]] ~~capable of~~ for inducing the slide [[(4)]] to move in axial translation ~~for her~~ with ~~the~~ axial rotation of the ~~aforementioned~~ base [[(2)]] ~~in comparison with~~ relative to the tubular body [[(3)]], the axial rotation of the base [[(2)]] ~~with respect~~ relative to the tubular body ~~being in addition capable of~~ further inducing the slide [[(4)]] ~~in rotation~~ to rotate and ~~axial translation~~ axially translate simultaneously ~~in comparison~~ relative to the tubular body [[(3)]], ~~characterized in that~~ ~~the~~ a height [[(H1)]] of the slide [[(4)]] and ~~the~~ a height [[(H2)]] of the means of guidance ~~are~~ being less than or equal to ~~the~~ an external height [[(H3)]] of the base [[(2)]].

2. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to claim 1, ~~characterized in that~~ wherein the means of guidance [[(20)]] ~~require~~ includes at least [[a]] one rectilinear guiding groove [[(21a, 21b)]] which ~~is adjusted~~ extends longitudinally ~~in~~ along at least one portion of ~~the~~ an inside tube [[(22)]] ~~extending in a~~ which extends concentrically ~~way to the~~ in an interior of the base [[(2)]], ~~each~~ the guiding groove [[(21a, 21b)]] ~~being able to cooperate~~ cooperating in a running ~~relative~~ relationship to the means of ~~guiding~~ guidance [[(41a, 41b)]] interdependent with the slide [[(4)]].

3. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~one of the claims 1 or 2~~ claim 1, ~~characterized in that~~ wherein the slide [[(4)]] ~~requires~~ includes a means of centering [[(40)]] ~~capable of~~ cooperating by contact with ~~the~~ an internal surface [[(34)]] of the tubular body [[(3)]].

4. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to claim 3, ~~characterized in that~~ wherein the means of centering [[(40)]] ~~require~~ includes at least two means of centering [[(43a, 43b, 43c, 43d)]] regularly spaced on ~~the~~ an external surface of ~~the superior~~ an upper end of the slide [[(4)]].

5. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~any of the claims 1 through 4~~ claim 1, ~~characterized in that~~ wherein the means of guidance ~~require in addition~~ includes longitudinal and rectilinear ~~storing~~ grooves [[(23a, 23b)]] which ~~are capable of receiving~~ receive the means of centering [[(43a, 43b, 43c, 43d)]] when the slide [[(4)]] is retracted to the interior of the base [[(2)]].

6. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~one of the claims 4 or 5~~ claim 4, ~~characterized in that~~ wherein the means of centering [[(43a, 43b, 43c, 43d)]] are ~~able to be placed~~ received in the guiding grooves [[(21a, 21b)]] ~~designed~~ to guide the slide [[(4)]] ~~in~~ along the interior of the base [[(2)]].

7. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~any of the claims 4 through 6~~ claim 4, ~~characterized in that~~ wherein the means of centering [[(43a, 43b, 43c, 43d)]] ~~are able to~~ cooperate by contact with ~~the~~ an edge [[(37)]] ~~interdependent~~ interacting with the ~~superior~~ upper end of the tubular body [[(3),]] ~~in order~~ to limit ~~towards the exterior~~ the course of the slide [[(4)]].

8. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~any of the claims 2 through 7~~ claim 2, ~~characterized in that each~~ wherein the means of guiding [[(41a, 41b)]] have ~~superior~~ larger dimensions ~~to those of the~~ than storage grooves [[(23a, 23b)]] ~~designed to~~ which receive the means of centering [[(43a, 43b, 43c, 43d)]].

9. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~any of the claims 1 through 8~~ claim 1, ~~characterized in that~~ wherein the tubular body [[(3)]] is transparent.

10. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~any of the claims 1 through 9~~ claim 1, ~~characterized in that~~ wherein the tubular body [[(3)]] ~~presents itself in the form of~~ is a tube [[(30)]] with circular cross-sections, ~~while the~~ a ring-shaped ~~exereseenee~~ [[(31)]] ~~extending~~ rib extends radially from the external surface[[,]] ~~obviously~~ half-way up the body tube setting the limits for [[thus]] movement, a ~~inferior side~~ [[(32)]] ~~designed to~~ lower end of the body tube rotatably receives the base [[(2)]] ~~movable by rotation~~, and ~~a superior side~~ [[(33)]] ~~designed to~~ upper end of the body tube receives a removable cap [[(100)]] ~~in an obviously~~ of complementary form.

11. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~any of the claims 1 through 10~~ claim 1, ~~characterized in that~~ wherein the slide [[(4)]] is transparent.

12. (Currently Amended) ~~Rotating~~ The rotating case [[(1)]] according to ~~any of the claims 1 through 11~~ claim 1, ~~characterized in that it requires~~ further including: a cap ~~capable of attaching itself in a removable way~~ removably attached to ~~the superior~~ an upper end of the tubular body [[(3)]].

13. (New) A rotating case comprising:

a body tube defining a spiral groove along a lower interior surface thereof, the body tube defining an exterior rib centrally therearound;

a base having an outer portion which rotatably receives a lower end of the tubular body and abutting a lower surface of the rib and an inner portion which extends rotatably into the tubular body, the inner portion defining at least one longitudinal guide groove;

a slide having a longitudinal length which is less than or equal to a longitudinal length of the base, the slide being movably received in the base interior

portion, the slide including at least one or more projections which each engage one or more of the longitudinal guide groove and the spiral groove such that as the base rotates relative to the tubular body, the slide projections are cammed by the spiral groove to move upward in the tubular body and are restrained by the longitudinal guidance groove to move longitudinally.

14. (New) The rotating case according to claim 13 wherein the slide includes at least one detent projecting outward adjacent an upper end therefrom;

an upper end of the tubular body including an inward extending lip for engaging the detent to limit longitudinal movement of the slide; and

the base including at least one storing groove adjacent an upper end thereof to receive the detent when the slide is in a fully retracted position.